




Manufactured to match its big brothers Ledge and Strato, the Switchback is designed to be an accessible climber, an industry first! The lowest platform of the Switchback conforms to guidelines for transfer platforms. Manufactured with various handholds and climbing surfaces, the four sides all vary in climbing difficulty. The Switchback also accepts 3' slides, so reward the little ones that reach the summit!



**Switchback Climber  
1000031**

L: 6'-10" x W: 5'-1" x H: 3'-0"  
1,400 LBS



**Switchback Climber w/  
Slide Attachment  
1000033**



**Integrated Handholds**




**Embedded Fossils**

~ Dimensions and weights are approximate ~  
~ Heights shown from top of surfacing ~  
**User Group Age: 2-12**

## Installation Instructions

### Use Zone






Product: 1000031

### Included Items:

Item	Description	Quantity
Switchback Rock Climber	Play Equipment	1
Anchor Bolt 5/8" x 6"	Mounting Hardware	4

## Installation Instructions



~ All dimensions are approximate ~

**User Group Age: 5-12**

Last Revised 4/25/16



## Installation Instructions


**NOTE:** Read installation instructions thoroughly before starting installation process.

**Step 1:** Lay out the area and prepare the site for install. Concrete must be installed over a solid, level base. Check local soil condition and codes. See installation instructions sheet for minimum use zone requirements to ensure proper spacing and adequate surfacing area.

**Step 2:** Pour a concrete base for the Switchback Rock Climber. Refer to the typical slab section on the typical footing page. The concrete should be flush with the ground level. Allow time for the concrete to completely cure before continuing.

**Step 3:** Using an appropriate lull-type forklift or boom, place Switchback Rock Climber into final installation location. See the hardware recommendation page for information on anchoring equipment down to your slab. Refer to the surfacing manufacturer for installation of an approved impact attenuating play surface around the Switchback Rock Climber with a minimum of 6 feet in every direction.


**Note:** See separate installation instructions for Switchback Slides when installing Switchback Rock Climber product number 1000033.



**Typical 8" Concrete Slab Section**  
Check Local Soil Conditions  
(Not to Scale)

### NOTES PRIOR TO CONSTRUCTION:

- Use appropriate equipment to lift and move the play equipment.
- Check local codes and requirements prior to digging or installing any equipment.



## Installation Instructions


**Step 4:** Locate your anchor bolts, supplied by Cre8Play. Using the proper standard drill bit size noted in the installation table, drill the concrete to the appropriate hole depth (C).

**Step 5:** Insert the anchor bolt into the hole and tighten until the bolt is fully seated. Do NOT over tighten the anchor bolts.


Installation Table

Anchor Bolt Size	ANSI Standard Drill Bit Diameter	Anchor Head (Socket Size) Diameter (A)	Minimum Embedment (B)	Hole Depth (C)
5/8" x 6"	1/2"	13/16"	5 1/2"	6 1/2"


Anchor Bolt (Large Diameter Tapcon)  
Installation:




Mounting Detail  
(Not to Scale)



Step 1: Drill



Step 2: Anchor



**NOTE:** Always wear eye protection appropriate to the task at hand.